

Example/voorbeeld **130-160** = length/lengte **130mm** spring rate/veer constante **160 N/mm** of **Kg/cm**

Inner diameter spring / binnen diameter veer

60 mm					70 MM		80MM	51MM
70-40	120-200	150-50	200-45	250-70	80-20	200-30	120-50	120-62,5
70-50	120-240	150-60	200-50	250-80	80-30	200-40	120-60	120-71,4
70-65	120-260	150-65	200-55	250-90		200-50	120-70	120-80,4
	120-280	150-70	200-60		90-22	200-55		120-89,3
80-15	120-290	150-80	200-70	270-35		200-60	200-20	120-98,2
80-20	120-300	150-90	200-80	270-40	110-20	200-70	200-30	120-107
80-80	120-310	150-100	200-90			200-80	200-40	120-116
80-90	120-320	150-110		280-30	120-50	200-90	200-50	120-125
80-100		150-120	220-20		120-60		200-60	120-133,9
80-115	130-70	150-130	220-22	300-25	120-70	220-40	200-70	120-142,8
80-120	130-80	150-140	220-25	300-30		220-45		120-151,8
80-125	130-90	150-150	220-30	300-35	130-90	220-50	280-50	120-161
	130-100	150-160	220-35	300-40	130-100	220-60	280-60	
100-3	130-110	150-170	220-40	300-45	130-110	220-80	280-70	130-60
100-5	130-130	150-180	220-45	300-60	130-120	220-90	46MM	130-70
100-20	130-140	150-190	220-50	300-70	130-130	220-100	80-6	130-80
100-70	130-150	150-200	220-55	300-80	130-140	220-110		130-90
100-80	130-160	150-220	220-60		130-160		180-40	130-100
100-85	130-170	150-240	220-70	330-20		240-40	180-50	130-110
100-90	130-180		220-80	330-25	140-170	240-45	180-60	
100-95	130-190	160-30		330-30		240-50	180-90	150-140
100-100	130-200	160-40	230-25	330-35	150-90	240-60	180-100	150-180
100-105	130-220		230-30	330-40	150-100	240-70	180-110	150-200
100-110	130-240	180-20	230-40	330-45	150-110	240-80	180-120	
100-120		180-25	230-45	330-50	150-120	240-90	180-130	220-70
100-125	140-80	180-30	230-50	330-55	150-130		180-140	220-80
100-130	140-82	180-40	230-55	330-60	150-140	280-50	180-150	220-100
100-135	140-84	180-50	230-60	330-65	150-150	280-60	180-160	
100-140	140-86	180-60	230-70		150-160	280-70		240-45
100-150	140-88	180-70		400-20	150-170		200-24	240-50
100-160	140-90	180-80	240-50	400-22	150-180	300-25	200-40	240-55
100-170	140-100	180-90	240-60	400-24	150-190	300-30	200-50	240-100
100-180	140-110	180-100	240-70	400-26		300-35	200-85	240-110
	140-120	180-110	240-75	400-28	160-80			240-120
110-260	140-130	180-120		400-30		330-50	220-65	240-130
110-270	140-140	180-130	250-25	400-40	180-80			
	140-150	180-140	250-30	400-42	180-90			
120-50	140-160	180-160	250-35	400-44	180-100			
120-60	140-170		250-40	400-55	180-110			
120-70	140-180	200-17	250-42		180-120			
120-80	140-190	200-20	250-45	440-55				
120-90	140-200	200-25	250-50					
120-140	140-220	20-30	250-55					
120-160		200-35	250-60					
120-190		200-40	250-65					

